

**LAW OFFICES
STAAS & HALSEY LLP**

Telephone
(202) 434-1500

700 Eleventh Street, N.W.
Suite 500
Washington, D.C. 20001

Facsimile
(202) 434-1501

FACSIMILE TRANSMISSION *2821*

June 16, 2003

TO: USPTO

ATTN: Examiner Tho Gia Phan

FAX NO.: 703.308.7722

FAX RECEIVED

TELEPHONE: 703.308.3051

FROM: H. J. Staas

JUN 16 2003

RE:

TECHNOLOGY CENTER 2800

YOUR REFERENCE: 09/986,949

OUR DOCKET: 1450.1012

NO. OF PAGES (Including this Cover Sheet)

PRIVILEGED & CONFIDENTIAL

The information contained in this communication is confidential, may be attorney-client privileged, and is intended only for the use of the addressee(s). Unauthorized use, disclosure or copying is strictly prohibited. If there are any problems with this transmission, please contact us immediately.

COMMENTS:

Enclosed is a copy of page 11 of the Amendment which was filed by Certificate of Mailing on May 30, 2003. It is believed that page 11 may have been omitted from the Amendment, as filed. Please attach this page to the Amendment.

Serial No. 09/986,949

Please ADD the following claims:

18. (NEW) A method of driving a plasma display device in which a first voltage is applied between sustain discharge electrodes so as to perform a discharge in a selected display cell, comprising:

removing wall charges, formed on an address electrode to select said display cell, by a sustain discharge performed between said sustain discharge electrodes.

19. (NEW) The method according to claim 18, wherein
said removing comprises applying a second voltage to at least one of said sustain discharge electrodes to form the wall charges and applying a third voltage to said address electrode to produce a self-erase discharge, and

said second voltage forms, on said address electrode by sustain discharge performed between said sustain discharge electrodes, wall charges which undergo self-erase discharge, between said address electrode and at least one of said sustain discharge electrodes, in said self-erase discharge.

20. (NEW) The method according to claim 19, wherein said removing comprises applying the second voltage to one of said sustain discharge electrodes and setting the other of said sustain electrodes at ground level.

21. (NEW) The method according to claim 2, wherein said second voltage is applied to one of said sustain discharge electrodes, and subsequently to the other electrode.

22. (NEW) The method according to claim 1, wherein said removing is performed between subfields, each subfield comprising reset, address, and sustain discharge intervals.

23. (NEW) A method of driving a plasma display device wherein a first voltage is applied between sustain discharge electrodes so as to perform a sustain discharge in a display cell, comprising: